



minipack[®]
THE ORIGINAL PIONEER



SEALPRO 50 PLC

E N G

ATM tray sealer - max tray dimensions 380x270x120 mm

DESCRIPTION

The **Sealpro 50 PLC** is the evolution of the Sealpro 50 heat sealer, equipped with a state-of-the-art multilingual PLC and a 4.3" color touchscreen panel.

In addition to the standard USB port which allows for program management and download of production programs, as well as the loading of any updates, it is also possible to request the installation of a photocell for printed film and a connection for remote assistance.

Like our entire range, the machine is extremely easy to use even for operators without specific technical skills.

Furthermore, the quick mold change system allows for format changes in just a few minutes and with minimal effort, thanks to special guides.



TECHNICAL FEATURES

Power supply	V	230V-400V 50hz
Maximum installed power	kW	2.5kW
Cycles per minute		up to 5
Maximum tray size	mm	380x270x120
Max roll width	mm	420 (skin 450)
Vacuum pump	m ³ /h	20-40-60
Number of storable programs		100
Color touch screen		Yes
Customizable mold		Yes
Rapid mold change		Yes
Modified atmosphere packaging (MAP)		Yes
Vacuum sensor		Yes
Machine dimensions	mm	810x550x1350
Weight	kg	150



OPTIONAL

- Touch screen PLC
- Printed film photocell
- Remote assistance kit
- Mold for 1 tray
- Mold for 2 trays
- Mold for 3 trays
- Mold for 4 trays
- Mold for 5 trays
- Mold for 6 trays
- Universal sealing plate
- Skin mold on cardboard 1 imprint (h. 45mm)
- Skin mold on cardboard 2 imprints (h. 45mm)
- Automatic trim winder standard or with rubberized roller
- Tray skin
- 10mm over skin on tray
- 40mm over skin on cardboard
- Automatic drawer opening closure
- Special voltage supplement
- Internal silent compressor