



**minipack® - torre**  
Packaging machines and systems

# Tunnel 50 Twin Inox

Version of Tunnel 50 Twin in stainless steel - Ideal for pharmaceutical and food sector



## DESCRIPTION

**TUNNEL 50 TWIN INOX** is designed to give effective answers to those who need to pack small products at high speeds, obtaining a safe and aesthetically optimal packaging. This **shrink wrap tunnel** boasts many features that contribute to this objective: the double heating chamber with separate regulation, an exceptional capacity of thermal insulation, the high speed of passage and retraction are all the qualities that make TUNNEL 50 TWIN INOX a perfect packaging machine to meet every need of packaging with extreme efficacy. The version entirely made of stainless steel is ideal for the needs of the food and pharmaceutical sector.

**minipack®-torre S.p.A.**

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



## TECHNICAL FEATURES

Electrical power supply	200V 50/60Hz 3Ph 208V 60Hz 3Ph 400V 50/60Hz 3Ph
MAX power installed	14 kW (200V) 15 kW (208V) 14,5 kW (400V)
Maximum current	38 A (200V) 43 A (208V) 21 A (400V)
MAX product size	400x190 mm xL. (The maximum length depends on the shape, conveyor belt speed and type of film, etc.)
Machine dimensions	2130x800x1460 mm
Machine weight (net/gross)	260/318 kg
Tunnel inlet dimensions	450x210 mm

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

## TECHNICAL DRAWING

[Lay-out Tunnel 50 Twin](#)



## • Features

- Manual regulation of conveyor height
- Digital display with 9 storable programs
- Selection of self rotation of conveyors rolls
- Double air flap
- Auto switch-off
- Exit roll conveyor
- Two independent heating rooms.